



## Pilot action models

Part number	Description Pipe size (inches)	CAPACITY 1 MIN. - MAX.					Layout	Port (Ø)	Weight (kg)	Master Carton
		R407C	R410A	R32	R134a	R290				
		kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.				
RV20AP20160000	VALV. DI INV. 20 UST 1-1/4 - 1	17.56 / 72.48 (4.99/ 20.61)	17.59 / 81.64 (5/ 23.21)	13.69 / 54.19 (3.89/ 15.41)	19 / 89.8 (5.4/ 25.53)	18.47 / 73.86 (5.25/ 21)	A	34.6	3.35	1
RV20AP22180000	VALV. DI INV. 20 UST 1-3/8 - 1-1/8	17.56 / 72.48 (4.99/ 20.61)	17.59 / 81.64 (5/ 23.21)	13.69 / 54.19 (3.89/ 15.41)	19 / 89.8 (5.4/ 25.53)	18.47 / 73.86 (5.25/ 21)	A	26.0	3.25	1
RV30AP24200000	VALV. DI INV. 30 UST 1-1/2 - 1-1/4	26.35 / 108.72 (7.49/ 30.91)	26.36 / 122.44 (7.5/ 34.81)	20.36 / 81.28 (5.79/ 23.11)	28.47 / 134.68 (8.09/ 38.3)	27.68 / 110.79 (7.87/ 31.5)	A	34.6	3.38	1
RV40AP28240000	VALV. DI INV. 40 UST 1-3/4 - 1-1/2	35.14 / 144.95 (9.99/ 41.21)	35.16 / 163.25 (10/ 46.42)	27.03 / 108.36 (7.69/ 30.81)	37.97 / 179.58 (10.8/ 51.06)	36.92 / 147.71 (10.5/ 42)	A	41	7.15	1
RV40AP26240000	VALV. DI INV. 40 UST 1-5/8 - 1-1/2	35.14 / 144.95 (9.99/ 41.21)	35.16 / 163.25 (10/ 46.42)	27.03 / 108.36 (7.69/ 30.81)	37.97 / 179.58 (10.8/ 51.06)	36.92 / 147.71 (10.5/ 42)	A	41	7.25	1
RV50AP34240000	VALV. DI INV. 50 UST 2-1/8 - 1-1/2	35.14 / 181.13 (9.99/ 51.5)	35.21 / 203.99 (10.01/ 58)	27.03 / 135.4 (7.69/ 38.5)	38.03 / 224.39 (10.01/ 58)	36.93 / 184.64 (10.5/ 52.5)	A	46.4	7.35	1
RV60AP42260000	VALV. DI INV. 60 UST 2-5/8 - 1-5/8	38.3 / 197.43 (10.89/ 56.14)	38.38 / 222.35 (10.91/ 63.22)	29.46 / 147.59 (8.38/ 41.96)	41.45 / 244.59 (11.79/ 69.54)	40.26 / 201.26 (11.45/ 57.23)	A	50.2	7.60	1

Part number	Description Pipe size (inches)	CAPACITY 2 MIN. - MAX.					Layout	Port (Ø)	Weight (kg)	Master Carton
		R407C	R410A	R134a	R32	R290				
		kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.	kW (US Ton) min./max.				
RV20AP20160000	VALV. DI INV. 20 UST 1-1/4 - 1	19.09 / 78.78 (5.43/ 22.4)	19.12 / 88.74 (5.44/ 25.23)	14.88 / 58.9 (4.23/ 16.75)	20.65 / 97.61 (5.87/ 27.75)	20.08 / 80.28 (5.71/ 22.83)	A	34.6	3.35	1
RV20AP22180000	VALV. DI INV. 20 UST 1-3/8 - 1-1/8	19.09 / 78.78 (5.43/ 22.4)	19.12 / 88.74 (5.44/ 25.23)	14.88 / 58.9 (4.23/ 16.75)	20.65 / 97.61 (5.87/ 27.75)	20.08 / 80.28 (5.71/ 22.83)	A	26.0	3.25	1
RV30AP24200000	VALV. DI INV. 30 UST 1-1/2 - 1-1/4	28.64 / 118.17 (8.14/ 33.6)	28.65 / 133.09 (8.15/ 37.84)	22.13 / 88.35 (6.29/ 25.12)	30.94 / 146.4 (8.8/ 41.63)	30.08 / 120.42 (8.55/ 34.24)	A	34.6	3.38	1
RV40AP28240000	VALV. DI INV. 40 UST 1-3/4 - 1-1/2	38.2 / 157.55 (10.86/ 44.8)	38.22 / 177.45 (10.87/ 50.45)	29.38 / 117.78 (8.35/ 33.49)	41.27 / 195.19 (11.74/ 55.5)	40.13 / 160.56 (11.41/ 45.65)	A	41	7.15	1
RV40AP26240000	VALV. DI INV. 40 UST 1-5/8 - 1-1/2	38.2 / 157.55 (10.86/ 44.8)	38.22 / 177.45 (10.87/ 50.45)	29.38 / 117.78 (8.35/ 33.49)	41.27 / 195.19 (11.74/ 55.5)	40.13 / 160.56 (11.41/ 45.65)	A	41	7.25	1
RV50AP34240000	VALV. DI INV. 50 UST 2-1/8 - 1-1/2	38.2 / 196.88 (10.86/ 55.98)	38.27 / 221.73 (10.88/ 63.04)	29.38 / 147.17 (8.35/ 41.85)	41.33 / 243.9 (10.01/ 58)	40.14 / 200.7 (11.41/ 57.07)	A	46.4	7.35	1
RV60AP42260000	VALV. DI INV. 60 UST 2-5/8 - 1-5/8	41.63 / 214.6 (11.84/ 61.02)	41.72 / 241.68 (11.86/ 68.72)	32.02 / 160.42 (9.1/ 45.61)	45.05 / 265.85 (12.81/ 75.59)	43.76 / 218.77 (12.44/ 62.2)	A	50.2	7.60	1