

**EASYREC-1**

Unità di recupero utilizzabile con CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze)

- Dispositivo di auto evacuazione (PURGE) che permette di cambiare facilmente il tipo di refrigerante.
- Dispositivo di arresto automatico al termine del refrigerante recuperato.
- Led di segnalazione (verde/ciclo eseguito con successo - rosso/allarme).
- Dispositivo di sicurezza pressione massima.
- Valvole di intercettazione che evitano la fuoriuscita di refrigerante.
- Manometri "pulse free" con vite di regolazione.
- Cilindro ceramico con tenuta in fibra di carbonio.
- Spia e filtro inclusi.
- Ampia grafica con istruzioni rapide di funzionamento.



Codice	Modello	Dimensioni con imballo	Peso con imballo
13001019	EASYREC-1	545 x 300 x 395 mm	15,5 kg


**Caratteristiche tecniche:**

Refrigeranti	CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze)
Alimentazione	220 - 240V AC 50 - 60 Hz
Potenza motore	550W
Max corrente assorbita	4A
Compressore	A pistone, a secco
Blocco automatico di sicurezza	38.5 bar/3850 kPa (558 psi)
Temperatura di esercizio	0 - 40 °C

Velocità di recupero	R1234ze- R134a	R502- R407C	R404A-R410A- R507-R32
Vapore	14 kg/h	15 kg/h	16 kg/h
Liquido (recupero)	96 kg/h	108 kg/h	132 kg/h
Push-pull	276 kg/h	336 kg/h	378 kg/h


**Ricambi e accessori**


Rif	Codice	Modello	Descrizione	Dimensioni	Peso
A	14015008	MG-111	Filtro disidratatore (1/4" SAE M-M)	100 x 40 x 40 mm	0,28 kg
A	14015041	MG-111-A	Filtro disidratatore con allumina (1/4" SAE M-M)	100 x 40 x 40 mm	0,28 kg
B	14015013	XH412	Filtro disidratatore "alta capacità" (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
B	14015042	XH412-A	Filtro disidratatore con allumina "alta capacità" (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
C	14020014001	G19020-WIG	Kit di 10 guarnizioni per tubi flessibili 1/4" SAE	160 x 90 x 10 mm	0,02 kg
D	06071013003	GYSS/4-4/6/Y	Tubo collegamento filtro 1/4" SAE 150 mm	250 x 50 x 50 mm	0,16 kg
E	13008026	REC026	Spia liquido/umidità	90 x 40 x 50 mm	0,17 kg

**EASYREC-1**

Recovery unit suitable for CFC, HCFC, HFC and HFO (included R32 and R1234ze)

- Self-evacuation system (PURGE) which allows to change the type of refrigerant easily.
- Automatic stop of the unit when there is no refrigerant available in the system.
- Signal LED (green/cycle performed successfully - red/alarm).
- Safety device for maximum pressure.
- Two cut-off valves to prevent refrigerant discharge.
- "Pulse free" gauges with regulation screw.
- Ceramic cylinder with carbon fiber seal.
- Sight glass and filter included.
- Wide graphics with quick functioning instructions.



Code	Model	Dimensions	Weight
13001019	EASYREC-1	545 x 300 x 395 mm	15,5 kg

**Technical features**

Refrigerant	CFC, HCFC, HFC and HFO (included R32 and R1234ze)
Power supply	220 - 240V AC 50 - 60 Hz
Motor power	550W
Maximal current draw	4A
Compressor	Piston-type and oil less
Automatic safety shut-off	38.5 bar/3850 kPa (558 psi)
Operating temperature	0 - 40 °C

Recovery rate	R1234ze- R134a	R502- R407C	R404A-R410A- R507-R32
Vapour	14 kg/h	15 kg/h	16 kg/h
Liquid (recovery)	96 kg/h	108 kg/h	132 kg/h
Push-pull	276 kg/h	336 kg/h	378 kg/h


**Spare parts and accessories**


Ref	Code	Model	Description	Dimensions	Weight
A	14015008	MG-111	Filter drier (1/4" SAE M-M)	100 x 40 x 40 mm	0,28 kg
A	14015041	MG-111-A	Filter drier (1/4" SAE M-M) with alumina	100 x 40 x 40 mm	0,28 kg
B	14015013	XH412	"High capacity" filter drier (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
B	14015042	XH412-A	"High capacity" filter drier (1/4" SAE M-M) with alumina	250 x 80 x 80 mm	1,10 kg
C	14020014001	G19020-WIG	Kit 10 gaskets for 1/4" SAE flexible hoses	160 x 90 x 10 mm	0,02 kg
D	06071013003	GYSS/4-4/6/Y	Connection hose for filter 1/4" SAE 150 mm	250 x 50 x 50 mm	0,16 kg
E	13008026	REC026	Sight glass	90 x 40 x 50 mm	0,17 kg