

PULSAIR 4

Air regulator

Technical Data Sheet



Description

The Air regulator PULSAIR 4 is a air regulator without gauge plug.



PULSAIR 4

Air regulator


DN		Ref.	Weight Kg
"	mm		
1 1/4	33/42	149B33	0,100

Technical features

Operating temperature	0 °C to 40 °C
Permissible operating pressure (PFA) in water	10 bar
Connection	Male 1"1/4, BSP thread
Mediums	Clear water

Nomenclature and materials

N°	Designation	Materials	EURO	ANSI
1	Body	POM (polyacetal)		
2	Float	PP (polypropylene)		
3	Seal	EPDM		
4	Pin	Brass (CW614N)		




Approvals

International construction Standards :
Thread connection NFE 03-005 - ISO 228

Sizing

DN		L	H
"	mm	mm	mm
1/4 male	33/42	172	46



PULSAIR 4

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



A WATTS Brand

Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France

Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42

contact@wattswater.com • www.socla.com

ISO 9001 version 2015 / ISO 18001