

VALVOLE A SFERA MOTORIZZATE
 MOTORIZED BALL VALVES

2 VIE - MOTORE UNIDIREZIONALE
 - WAYS WITH **UNIDIRECTIONAL** ACTUATOR

Corpi valvola - Valve bodies	Attacchi Connections	Kv (m ³ /h)	Ø	Codice Code
	Femmina <i>Female</i>	12,5	1/2"	632 FN
		15,6	3/4"	602 FN
		31,3	1"	612 FN
		50,0	1" 1/4	622 FN
		98,0	1" 1/2	642FN
	Maschio <i>Male</i>	12,5	3/4"	602 MN
		15,6	1"	612 MN
		31,3	1" 1/4	622 MN
		50,0	1" 1/2	642 MN
	Femmina / Bocchettone <i>Female / Pipe-unions</i>	12,2	1/2"	632 FBN
		15,1	3/4"	602 FBN
		30,6	1"	612 FBN
		49,1	1" 1/4	622 FBN
		96,0	1" 1/2	642 FBN
	Bocchettone <i>Pipe-unions</i>	12,0	1/2"	632 BN
		14,9	3/4"	602 BN
30,0		1"	612 BN	
48,2		1" 1/4	622 BN	
94,1		1" 1/2	642 BN	

Servomotori - Actuators	Controllo Control	Contatto Aux. Aux. switch	Alimentaz. Supply	Tempo corsa Running time	Codice Code
<p>Rotazione unidirezionale <i>Unidirectional rotation</i></p> <p>OK NO</p> <p>OK OK</p>	Comando a 3 FILI <i>3-WIRES Control</i>	Senza contatto aux. <i>No aux. switch</i>	230V	60"	P6A2
			24V		P6S2
			230V	15"	P6A2W
			24V		P6S2W
			230V	8"	P6A2X
			24V		P6S2X
		1 contatto aux. <i>1 aux. switch</i>	230V	60"	P6B2
			24V		P6C2
			230V	15"	P6B2W
			24V		P6C2W
			230V	8"	P6B2X
			24V		P6C2X
	2 contatti aux. <i>2 aux. switch</i>	230V	60"	P6X2	
		24V		P6Y2	
		230V	15"	P6X2W	
		24V		P6Y2W	
		230V	8"	P6X2X	
		24V		P6Y2X	
	Comando a 2 FILI <i>2-WIRES Control</i>	Senza contatto aux. <i>No aux. switch</i>	230V	60"	T6A2
			24V		T6S2
			230V	15"	T6A2W
			24V		T6S2W
			230V	8"	T6A2X
			24V		T6S2X
1 contatto aux. <i>1 aux. switch</i>		230V	60"	T6B2	
		24V		T6C2	
		230V	15"	T6B2W	
		24V		T6C2W	
		230V	8"	T6B2X	
		24V		T6C2X	

ACCESSORI <i>Accessories</i>	Ø M Ø M	Ø F/ BOC. Ø F/ P.U.	Codice Code
Distanziale per coibentazione semplice <i>Spacer for pipes insulation without manual override</i>	Tutti <i>All</i>		K2S6
Guscio di coibentazione in polietilene reticolato espanso <i>Insulation shell made off crossed linked polyethylene foam</i>	3/4"-1"	1/2" - 3/4"	GC02
	1"1/4	1"	GC12
	1"1/2	1"1/4	GC22
	-	1"1/2	GC42

