

## mini valvole a sfera da barra

## serie **COMPACT**

### CARATTERISTICHE TECNICHE

<b>Materiali</b>	<ul style="list-style-type: none"> <li>• Corpo valvola: CW 614N UNI-EN 12164, ricavato da barra esagonale profilata</li> <li>• Asta: CW 614N UNI-EN 12164</li> <li>• Ghiera: CW 614N UNI-EN 12164</li> <li>• Sfera: CW 614N UNI-EN 12164 nichelata</li> <li>• Guarnizioni della sfera: PTFE (Teflon) NBR (per serie Flex)</li> <li>• Anello di tenuta asta: OR NBR 70</li> <li>• Leva: Nylon 66 caricato vetro</li> </ul>
<b>Finitura</b>	<ul style="list-style-type: none"> <li>• Versione MF/FF: cromata</li> <li>• Versione maschio/maschio: nichelata</li> </ul>
<b>Manovra</b>	<ul style="list-style-type: none"> <li>• Rotazione di 90° della leva                             <ul style="list-style-type: none"> <li>o del cacciavite</li> </ul> </li> </ul>
<b>Diametro nominale</b>	<ul style="list-style-type: none"> <li>• Da 6 mm a 18 mm</li> </ul>
<b>Pressione di esercizio</b>	<ul style="list-style-type: none"> <li>• 0-10 bar a 90°C</li> </ul>
<b>Limiti di temperatura</b>	<ul style="list-style-type: none"> <li>• -10°C + 90°C</li> </ul>
<b>Direzione di passaggio</b>	<ul style="list-style-type: none"> <li>• Bidirezionale</li> </ul>
<b>A richiesta</b>	<ul style="list-style-type: none"> <li>• Leve in alluminio</li> <li>• O.R. (Viton) - EPDM</li> <li>• Materiale in sostituzione del CW 614N UNI-EN 12164: Anticorrosivo CW 602N UNI-EN 12165</li> <li>• Finiture: sabbiato cromato, cromato spazzolato</li> </ul>

## miniball valves made from bar

## **COMPACT** line

### TECHNICAL FEATURES

<b>Materials</b>	<ul style="list-style-type: none"> <li>• Valve body: CW 614N UNI-EN 12164, made from profiled hexagonal bars</li> <li>• Spindle: CW 614N UNI-EN 12164</li> <li>• Locking ring: CW 614N UNI-EN 12164</li> <li>• Ball: CW 614N UNI-EN 12164 nickel plated</li> <li>• Ball gaskets: PTFE (Teflon) NBR (for Flex series)</li> <li>• Spindle sealing ring: OR NBR 70</li> <li>• Lever: glass-charged nylon 66</li> </ul>
<b>Finish</b>	<ul style="list-style-type: none"> <li>• MF/FF version: chrome plated</li> <li>• Male/male version: nickel plated</li> </ul>
<b>Maneuver</b>	<ul style="list-style-type: none"> <li>• 90° rotation of lever or screwdriver</li> </ul>
<b>Nominal diameter</b>	<ul style="list-style-type: none"> <li>• From 5 to 18 mm</li> </ul>
<b>Working pressure</b>	<ul style="list-style-type: none"> <li>• 0-10 bar at 90°C</li> </ul>
<b>Temperature limits</b>	<ul style="list-style-type: none"> <li>• -10°C + 90°C</li> </ul>
<b>Passage direction</b>	<ul style="list-style-type: none"> <li>• Two-way</li> </ul>
<b>On request</b>	<ul style="list-style-type: none"> <li>• Levers in aluminium</li> <li>• O.R. (Viton) - EPDM</li> <li>• Corrosion resistant W602N UNI-EN 12165 (DZR)</li> <li>• Finish: sandblasted chrome plating brushed chrome plating</li> </ul>



### A RICHIESTA ON REQUEST



CACCIAVITE  
SCREWDRIVER SLOT



LEVA LUNGA  
LONG LEVER

# 405



MINI VALVOLA A SFERA MASCHIO FEMMINA  
DA BARRA ESAGONALE CROMATA  
CON LEVA NYLON CARICATO VETRO

*MALE/FEMALE MINIBALL VALVE  
FROM HEXAGONAL CHROME PLATED BAR  
WITH GLASS-CHARGED NYLON LEVER*

		PEZZI PER SCATOLA	PIECES PER CARTON
COD. 011100100	1/8"x6	30 IN SACCHETTI DA 5	30 IN 5 PIECE BAGS
COD. 011100101	1/4"x8	30 IN SACCHETTI DA 5	30 IN 5 PIECE BAGS
COD. 011100103	3/8"x12	30 IN SACCHETTI DA 5	30 IN 5 PIECE BAGS
COD. 011100106	1/2"x15	25 IN SACCHETTI DA 5	25 IN 5 PIECE BAGS
COD. 011100108	3/4"x18	15 IN SACCHETTI DA 5	15 IN 5 PIECE BAGS