Net weight	0.01 kg
Approval	EAC LLC CDC TYSK
Category	Art. 4, par. 3
Design	SAE flare only
Fluid Group	1
Orifice size	06
Packing format	Multi pack
Parts Program name	T2/TE2
Product accessories	TXV accessories

0.02 kg

**Gross weight** 

Rated cap. R404A, Range B [kW]	6.9 kW
Rated cap. R404A, Range B [TR]	2 tons
Rated cap. R404A, Range N [kW]	15.5 kW
Rated cap. R404A, Range N [TR]	4.4 tons
Rated cap. R407C, Range N [kW]	19.7 kW
Rated cap. R407C, Range N [TR]	5.6 tons
Rated cap. R507, Range B [kW]	6.9 kW
Rated cap. R507, Range B [TR]	2 tons
Rated cap. R507, Range N [kW]	15.5 kW

5702422050292

EAN

Product family name	Product family name T2			
		Rated cap. R507, Range N [TR]	4.4 tons	
Product group	Expansion valves	Rated cap. R513A, Range N [kW]	8.6 kW	
Product name	Orifice for expansion valve	Rated cap. R513A, Range N [TR]	2.5 tons	
Quantity per packing format	25 pc			
Rated cap. cond. Range N [IMP]	tcond=100 °F tevap=40 °F tliq=98 °F	Refrigerants	R22/R407C R23 R236fa R407C R134a/R513A	
Rated cap. cond. Range N [SI]	tcond=38 °C tevap=4.4 °C tliq=37 °C		R407A R448A R449A R452A	
Rated cap. R134a, Range N [kW]	10.1 kW		R404A/R507A	
Rated cap. R134a, Range N [TR]	2.9 tons	Serviceable	No	
Rated cap. R22, Range B [kW]	8.7 kW	Temperature range [°C] [Max]	10 °C	
Rated cap. R22, Range B [TR]	2.5 tons	Temperature range [°C] [Min]	-40 °C	

Rated cap. R22, Range N [kW]	19.7 kW	Temperature range [°F] [Max]	50 °F
Rated cap. R22, Range N [TR] 5.6 tons	5.6 tons	Temperature range [°F] [Min]	-40 °F
		Туре	Orifice
		Used for product	T 2 TE 2