



PER PORTE TAMPONE

Chiusure in materiale composito ad elevata resistenza alle basse temperature ed alla corrosione

- Sistema di regolazione sul chiavistello (brevettato)
- Nessun ingombro della luce porta
- Cilindro a profilo europeo (chiave maestra su richiesta)
- Dispositivo interno di apertura con sgancio a pulsante
- Aggancio automatico
- Versione antimicrobica con tecnologia I-on® su richiesta
- **Conforme ai requisiti della norma EN 179**

FOR OVERLAPPING DOORS

Fasteners in composite material, low temperature and corrosion resistant

- Adjusting system on the catch (patented)
- No door clearance encumbrance
- Europrofile cylinder (master key on request)
- Photoluminescent inside release push-button
- Automatic catching device
- Antimicrobial version with I-on® technology on request
- **In compliance with EN 179 rules**

DATI TECNICI

- Spessore porta: da 50 a 160 mm
- Regolazione del chiavistello: +/- 6 mm
- Colori standard - chiusura esterna: corpo/grigio RAL 7012 - maniglia/grigio RAL 7004

TECHNICAL DATA

- Door thickness: from 50 to 160 mm
- Strike adjustment: +/- 6 mm
- Standard colours - external fastener: body/grey RAL 7012 - handle/grey RAL 7004



CODICE | CODE SERIE | SERIES DESCRIZIONE | DESCRIPTION

Chiusure serie 5000AB per porte a tampone | Fasteners series 5000AB for overlapping doors

R020495	5025	Chiusura 5025 AB senza chiave Fastener 5025 AB without key
R020496	5325	Chiusura 5325 AB con chiave Fastener 5325 AB with key
R021426	5325 I-on®	Chiusura 5325 AB I-on® con chiave Fastener 5325 AB I-on® with key
R020497		KIT 5000AB 50/60 mm
R020499		KIT 5000AB 61/80 mm
R020501		KIT 5000AB 81/100 mm
R020502		KIT 5000AB 101/120 mm
R020503		KIT 5000AB 121/140 mm
R020536		KIT 5000AB 150 mm