







# R-404A

# POSITIVE COMMERCIAL COOLING

	Models	Capacity cm <sup>3</sup>	Motor type	EN12900 (RTG 20 °C) – 50 Hz						
				Evaporation T°						
				-15	-10	-5	0	5	10	15
	THB4428Z	5,2	CSIR	324	401	488	588	701	829	975
	<b>New</b> AE4425Z	4,24	CSIR	257	326	407	502	613	741	889
	<b>New</b> AE4430Z	5,16	CSIR	320	404	500	611	740	888	1057
	<b>New</b> AE4440Z	6,69	CSIR	433	546	676	826	1000	1199	1427
	<b>New</b> AE4450Z	8,85	CSIR	576	720	885	1074	1289	1534	1812
	<b>New</b> AE4460Z	10,33	CSR	713	875	1062	1275	1519	1799	2117
	<b>New</b> AE4470Z	12,01	CSR	843	1035	1251	1495	1773	2088	2447
	CAJ/TAJ9480Z	15,2	CSR / TRI	920	1159	1434	1752	2117	2535	3013
	CAJ/TAJ9510Z	18,3	CSR / TRI	1158	1453	1794	2187	2639	3157	3749
	CAJ/TAJ9513Z	24,2	CSR / TRI	1423	1827	2290	2819	3422	4106	4879
	CAJ/TAJ4517Z	25,95	CSR / TRI	1648	2070	2552	3104	3736	4459	5283
	CAJ/TAJ4519Z	34,45	CSR / TRI	2129	2699	3342	4069	4896	5833	6896
	FH/TFH 4522Z	39,9	CSR / TRI	1951	2617	3380	4257	5262	6411	7720
	FH/TFH 4524Z	43,5	CSR / TRI	2299	3048	3889	4833	5887	7059	8359
	FH/TFH 4531Z	56,6	CSR / TRI	3055	3968	4991	6143	7444	8916	10580
	FH/TFH 4540Z	74,2	CSR / TRI	4043	5173	6437	7861	9471	11292	13349
	TAG4546Z	90,2	TRI	4035	5457	7122	9061	11307	13892	16850
	TAG4553Z	100,7	TRI	4633	6220	8062	10202	12684	15550	18845
	TAG4561Z	112,5	TRI	5389	7107	9082	11363	13998	17036	20527
	TAG4568Z	124,4	TRI	6534	8449	10672	13233	16166	19502	23273
TAG4573Z	135	TRI	7132	9167	11520	14236	17358	20930	24997	
<b>New</b> TAG4581Z	145	TRI	7833	10072	12659	15647	19095	23033	27537	

	Models	Capacity cm <sup>3</sup>	Motor type	EN12900 (RTG 20 °C) – 50 Hz						
				Evaporation T°						
				-15	-10	-5	0	5	10	15
	RG/HGA 4467Z	9,5	CSR	754	915	1100	1313	1556	1833	2150
	RG/HGA 4480Z	11,5	CSR	908	1100	1320	1573	1863	2195	2573
	RG/HGA 4492Z	12,8	CSR	1036	1256	1507	1796	2128	2509	2942
	RG/HGA 4512Z	16,1	CSR	1278	1553	1867	2227	2639	3109	3645

	Models	Capacity cm <sup>3</sup>	Motor type	EN12900 (RTG 20 °C) – 50 Hz						
				Evaporation T°						
				-15	-10	-5	0	5	10	15
	VSA9510Z	26,55	CSR / TRI	1910	2339	2847	3441	4132	4929	5842
	VSA9514Z	36,05	CSR / TRI	2539	3145	3844	4649	5570	6620	7812
	VSA9517Z	42,77	CSR / TRI	3503	4247	5111	6111	7262	8579	10077
	VSA9521Z	50,14	CSR / TRI	4184	5085	6111	7281	8613	10124	11905
	VSA9524Z	57,68	TRI	4529	5505	6637	7944	9447	11168	13128
	VSA9528Z	68,8	TRI	5637	6823	8178	9727	11491	13394	15758
	VSA9536Z	82,6	TRI	7191	8676	10364	12281	14456	16918	19695
VSA9544Z	106,5	TRI	8853	10701	12824	15259	18040	21203	24783	

In a constant endeavour to improve its products, TECUMSEH EUROPE reserves the right to change any information contained in the catalogue without prior warning.