

ZR40K3E-PFJ

HFC, R-407C, Dew Point, 50 Hz, 1 - Phase, 220/240 V
Air Conditioning

Performance

Evap(°F)/Cond(°F)	<u>45/130</u>	<u>45/100</u>
RG(°F)/Liq(°F)	<u>65/115</u>	<u>65/85</u>
Capacity (Btu/hr):	31800	38900
Power (Watts):	3040	2000
Current (Amps):	14.3	9.7
EER (Btu/Wh):	10.5	19.4
Mass Flow (lbs/hr):	462.0	482.0
Sound Power(dBA):	68 Ave	73 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2005-04-15	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	3.309
Bore Size (in):	0.0	Displ (ft ³ /hr):	333.1964
Stroke (in):	0.0		
Overall Length (in):	9.567	Mounting Length (in):	7.5
Overall Width (in):	9.567	Mounting Width(in):	7.5
Overall Height (in):	16.25	Mounting Height (in):	16.5*
Suction Size (in):	3/4 Stub		
Discharge Size (in):	1/2 Stub		
Initial Oil Charge (oz):	42		
Oil Recharge (oz):	38		
Net Weight (lbs):	61.5		
Internal Free Volume (in ³):	182.0		
HorsePower			
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	100.0	MCC (Amps):	24.0	UL File No.:	
LRA-Half Winding:		RPM:	2900	UL File Date:	14-Jun-1994
LRA-Low*:	90.0	Max Operating Current:	23.1	CSA File No.:	
RLA(=MCC/1.4; use for contactor selection): 17.1					
RLA (=MCC/1.56; use for breaker & wire size selection): 15.4					
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-134a HFC	60	1	265	Air Conditioning
R-407C HFC	60	1	265	Air Conditioning
R-134a HFC	50	1	220/240	Air Conditioning