

DI+CANALIZZ. STD R32

UNITA' INTERNA	RAV-RM561BTP-E	RAV-RM801BTP-E	RAV-GM901BTP-E	RAV-RM1101BTP-E	RAV-RM1401BTP-E	RAV-RM1601BTP-E	RAV-RM1101BTP-E	RAV-RM1401BTP-E	RAV-RM1601BTP-E	
UNITA' ESTERNA	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM901ATP-E	RAV-GM1101ATP-E	RAV-GM1401ATP-E	RAV-GM1601ATP-E	RAV-GM1101AT8P-E	RAV-GM1401AT8P-E	RAV-GM1601AT8P-E	
RAFFRESCAMENTO	Monofase	Monofase	Monofase	Monofase	Monofase	Monofase	Trifase	Trifase	Trifase	
Capacità nominale	kW 5.00	6.70	8.0	9.50	12.10	14.0	9.50	12.10	14.0	
Capacità min. - max.	kW 1,5-5,6	1,5-8,0	1,9 - 8,8	3,0-11,2	3,0-13,2	3,0-16,0	3,0-11,2	3,0-13,2	3,0-16,0	
Potenza assorbita (min. - nominale - max.)	kW 0,31-1,8-2,05	0,31-2,38-2,76	nd - 2,67 - nd	0,60-2,99-4,5	0,60-4,42-4,71	n.d.-5,13-n.d.	0,60-2,99-4,5	0,60-4,42-4,71	n.d.-5,13-n.d.	
Pdesignc	kW 5.00	6.70	8.00	9.50	12.10	14.00	9.50	12.10	14.00	
SEER	WW 5.28	5.20	6.10	5.28	5.36	5.30	5.28	5.36	5.30	
Classe di efficienza energetica	A	A	A++	A	-	-	A	-	-	
Consumo energetico stagionale	kWh 332.00	451.00	459.00	629.00	-	925.00	629.00	-	925.00	
RISCALDAMENTO										
Capacità nominale	kW 5.30	7.70	9.0	11.20	13.00	16.0	11.20	13.00	16.0	
Capacità min. - max.	kW 1,5-6,3	1,5-9,0	1,6 - 9,9	3,0-13,0	3,0-16,0	3,0-18,0	3,0-13,0	3,0-16,0	3,0-18,0	
Potenza assorbita (min. - nominale - max.)	kW 0,31-1,6-2,47	0,31-2,32-3,18	nd - 2,65 - nd	0,60-2,99-4,0	0,60-3,60-4,6	n.d.-4,69-n.d.	0,60-2,99-4,0	0,60-3,60-4,55	n.d.-4,69-n.d.	
Pdesignh	kW 2.80	5.10	6.30	7.60	7.60	8.00	7.60	7.60	8.00	
SCOP	WW 4.08	4.13	4.60	4.19	4.19	3.90	4.19	4.19	3.90	
Classe di efficienza energetica	H A+	A+	A++	A+	-	-	A+	-	-	
Consumo energetico stagionale	kWh 960.00	1728.00	1917.00	2537.00	-	2782.00	2537.00	-	2782.00	
UNITA' INTERNA	RAV-RM561BTP-E	RAV-RM801BTP-E	RAV-GM901BTP-E	RAV-RM1101BTP-E	RAV-RM1401BTP-E	RAV-RM1601BTP-E	RAV-RM1101BTP-E	RAV-RM1401BTP-E	RAV-RM1601BTP-E	
Portata Aria (a-m-b)	m³/h 800 - 630 - 480	1200 - 930 - 720	1700 - 1300 - 1000	2100 - 1650 - 1260	2100 - 16500 - 1260	2100 - 1740 - 1500	2100 - 1650 - 1260	2100 - 1650 - 1260	2100 - 1740 - 1500	
Prevalenza statica utile (min - nom - max)	Pa 30-30-120	30-30-120	30-40-120	30-50-120	30-50-120	30-50-120	30-50-120	30-50-120	30-50-120	
Livello di pressione sonora (b-m-a)	dB(A) 25-29-33	26-30-34	30-33-37	33-36-40	33-36-40	33-36-40	33-36-40	33-36-40	33-36-40	
Livello di potenza sonora (b-m-a)	dB(A) 40-44-48	41-45-49	45-48-52	48-51-55	48-51-55	54-58-63	48-51-55	48-51-55	54-58-63	
Pompa scarico condensa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	
Prevalenza pompa	mm 850.00	850.00	850.00	850.00	850.00	850.00	850.00	850.00	850.00	
Dimensioni (A x L x P)	mm 275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	
Peso	kg 23	30	40.00	40	40	40	40	40	40	
Flangia di mandata aria	Codice TCB-SF56C6BPE	TCB-SF80C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	
Numero Bocchette	2.00	3.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	
UNITA' ESTERNA	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM901ATP-E*	RAV-GM1101ATP-E	RAV-GM1401ATP-E	RAV-GM1601ATP-E*	RAV-GM1101AT8P-E	RAV-GM1401AT8P-E	RAV-GM1601AT8P-E*	
Portata Aria (a) (C-H)	m³/h 2400.00	2700.00	2900.00	4080.00	4200.00	6900.00	4080.00	4200.00	6900.00	
Livello di pressione sonora (C-H)	dB(A) 46-48	48-52	51-55	54-57	55-57	53-55	54-57	55-57	53-55	
Livello di potenza sonora (C-H)	dB(A) 63-65	65-69	68-72	70-74	70-74	70-72	70-74	70-74	70-72	
Intervallo di funzionamento (C)	°C -15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	
Intervallo di funzionamento (H)	°C -15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	
Dimensioni (A x L x P)	mm 550 x 780 x 290	550 x 780 x 290	630x800x300	890 x 900 x 320	890 x 900 x 320	1340x900x320	890 x 900 x 320	890 x 900 x 320	1340x900x320	
Peso	kg 40.00	44	47.00	68.00	68.00	94.00	69.00	69.00	94.00	
Compressore	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	
Refrigerante-Pre-carica Kg-TCO2Eq-GWP	R32-0,9-0,61-675	R32-1,3-0,88-675	R32-2,00-1,35-675	R32-2,1-1,42-675	R32-2,1-1,42-675	R32-2,4-1,62-675	R32-2,1-1,42-675	R32-2,1-1,42-675	R32-2,4-1,62-675	
Accoppiamento a cartella Gas	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	
Accoppiamento a cartella Liquido	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	
Lunghezza delle tubazioni (min-max)	m 5-30	5-30	5-50	5-50	5-50	5-50	5-50	5-50	5-50	
Dislivello massimo	m 30	30	30	30	30	30	30.00	30.00	30	
Lunghezza delle tubazioni senza carica aggiuntiva	m 20	20	30	30	30	30	30.00	30.00	30	
Alimentazione	V-ph-Hz 220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	415/380-3-50 380-3-60	415/380-3-50 380-3-60	415/380-3-50 380-3-60
Corrente massima	A 15.50	15.50	17.00	22.80	22.80	29.00	22.80	22.80	16.00	
Detraibilità fiscale										
Conto Termico					CT		CT			
C: Raffrescamento										
H: Riscaldamento										