

DI+CASSETTA STD 4V R32

UNITA' INTERNA	RAV-RM561UTP-E	RAV-RM801UTP-E	RAV-GM901UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E	RAV-RM1601UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E	RAV-RM1601UTP-E	
UNITA' ESTERNA	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM901ATP-E	RAV-GM1101ATP-E	RAV-GM1401ATP-E	RAV-GM1601ATP-E	RAV-GM1101AT8P-E	RAV-GM1401AT8P-E	RAV-GM1601AT8P-E	
	Monofase	Monofase	Monofase	Monofase	Monofase	Monofase	Trifase	Trifase	Trifase	
RAFFRESCAMENTO										
Capacità nominale	kW	5.00	6.70	8.00	9.50	12.00	14.00	9.50	12.00	14.00
Capacità min. - max.	kW	1,5-5,6	1,5-8,0	1,9-8,8	3,0-11,2	3,0-13,2	3,0-16,0	3,0-11,2	3,0-13,2	3,0-16,0
Potenza assorbita (min. - nominale - max.)	kW	0,26-1,56-1,86	0,26-2,22-2,6	nd - 2,42 - nd	0,60-2,87-4,10	0,60-4,29-4,71	n.d.-4,49-n.d.	0,60-2,87-4,10	0,60-4,29-4,71	n.d.-4,49-n.d.
Pdesignc	kW	5.00	6.70	8.00	9.50	12.00	14.00	9.50	12.00	14.00
SEER	W/W	6.34	5.81	7.00	6.15	5.71	6.30	6.15	5.71	6.30
Classe di efficienza energetica		A++	A+	A++	A++	A+	-	A++	A+	-
Consumo energetico stagionale	kWh	276.00	403.00	389.00	540.00	736.00	778.00	778.00	778.00	778.00
RISCALDAMENTO										
Capacità nominale	kW	5.30	7.70	9.00	11.20	13.00	16.0	11.20	13.00	16.0
Capacità min. - max.	kW	1,5-6,3	1,5-9,0	1,6-9,9	3,0-13,0	3,0-16,0	3,0 - 18,0	3,0-13,0	3,0-16,0	3,0 - 18,0
Potenza assorbita (min. - nominale - max.)	kW	0,26-1,36-2,08	0,26-2,13-3,03	nd - 2,65 - nd	0,60-2,93-4,30	0,60-3,46-4,50	n.d.-4,43-n.d.	0,60-2,93-4,30	0,60-3,46-4,50	n.d.-4,43-n.d.
Pdesignh	kW	2.80	5.10	6.30	8.00	8.00	8.00	8.00	8.00	8.00
SCOP	W/W	4.60	4.42	4.60	4.28	4.29	4.35	4.28	4.29	4.35
Classe di efficienza energetica	H	A++	A+	A++	A+	A+	-	A+	A+	-
Consumo energetico stagionale	kWh	852.00	1615.00	1917.00	2616.00	2611.00	2575.00	2575.00	2575.00	2575.00
UNITA' INTERNA	RAV-RM561UTP-E	RAV-RM801UTP-E	RAV-GM901UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E	RAV-RM1601UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E	RAV-RM1601UTP-E	
Portata Aria (a-m-b)	m³/h	1050 - 870 - 780	1230 - 960 - 810	1600-1170-900	2010 - 1440 - 1170	2100 - 1440 - 1230	2130- 2500 - 1260	2010 - 1440 - 1170	2100 - 1440 - 1230	2130- 2500 - 1260
Livello di pressione sonora (b-m-a)	dB(A)	28-29-32	28-31-35	33-36-40	33-38-43	34-38-44	36-40-45	33-38-43	34-38-44	36-40-45
Livello di potenza sonora (b-m-a)	dB(A)	43-44-47	43-46-50	48-51-55	48-53-58	49-53-59	51-55-60	48-53-58	49-53-59	51-55-60
Pompa scarico condensa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	inclusa
Prevalenza pompa**	mm	850.00	850.00	850.00	850.00	850.00	850.00	850.00	850.00	850.00
Dimensioni (A x L x P)	mm	256x840x840	256x840x840	319x840x840	319x840x840	319x840x840	319x840x840	319x840x840	319x840x840	319x840x840
Peso	kg	20.00	20.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
Griglia	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E	RBC-U31PGP(W)-E
Dimensioni della griglia (A x L x P)	mm	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950
Peso griglia	kg	4.20	4.20	4.20	4.20	4.20	4.20	4.20	4.20	4.20
UNITA' ESTERNA	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM901ATP-E	RAV-GM1101ATP-E	RAV-GM1401ATP-E	RAV-GM1601ATP-E	RAV-GM1101AT8P-E	RAV-GM1401AT8P-E	RAV-GM1601AT8P-E	
Portata Aria (a) (C-H)	m³/h	2400.00	2700.00	2900.00	4080.00	4200.00	6900.00	4080.00	4200.00	6900.00
Livello di pressione sonora (C-H)	dB(A)	46-48	48-52	51-55	54-57	55-57	53-55	54-57	55-57	53-55
Livello di potenza sonora (C-H)	dB(A)	63-65	65-69	68-72	70-74	70-74	70-72	70-74	70-74	70-72
Intervallo di funzionamento (C)	°C	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46	-15 + 46
Intervallo di funzionamento (H)	°C	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15	-15 + 15
Dimensioni (A x L x P)	mm	550 x 780 x 290	550 x 780 x 290	630x800x300	890 x 900 x 320	890 x 900 x 320	1340x900x320	890 x 900 x 320	890 x 900 x 320	1340x900x320
Peso	kg	40.00	44	47.00	68.00	68.00	94.00	69.00	69.00	94.00
Compressore	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary
Refrigerante-Pre-carica Kg-TCO2Eq-GWP	R32-0,9-0,61-675	R32-1,3-0,88-675	R32-2,00-1,35-675	R32-2,1-1,42-675	R32-2,1-1,42-675	R32-2,4-1,62-675	R32-2,1-1,42-675	R32-2,1-1,42-675	R32-2,4-1,62-675	
Accoppiamento a cartella Gas	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
Accoppiamento a cartella Liquido	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Lunghezza delle tubazioni (min-max)	m	5-30	5-30	5-50	5-50	5-50	5-50	5-50	5-50	5-50
Dislivello massimo	m	30	30	30	30	30	30	30.00	30.00	30
Lunghezza delle tubazioni senza carica aggiuntiva	m	20	20	30	30	30	30	30.00	30.00	30
Alimentazione	V-ph-Hz	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	220/240-1-50 220-1-60	415/380-3-50 380-3-60	415/380-3-50 380-3-60	415/380-3-50 380-3-60
Corrente massima	A	15.50	15.50	17.00	22.80	22.80	29.00	14.10	22.80	16.00
Detraibilità fiscale			0.65	0.65			0.65			
Conto Termico	CT		CT	CT	CT		CT	CT		
C: Raffrescamento										
H: Riscaldamento										
a: velocità ventilatore Alta										