Net weight	0.01 kg
Approval	EAC LLC CDC TYSK
Category	Art. 4, par. 3
Design	SAE flare only
Fluid Group	1
Orifice size	05
Packing format	Multi pack
Parts Program name	T2/TE2
Product accessories	TXV accessories

0.02 kg

Gross weight

Rated cap. R404A, Range B [kW]	5.9 kW
Rated cap. R404A, Range B [TR]	1.7 tons
Rated cap. R404A, Range N [kW]	13 kW
Rated cap. R404A, Range N [TR]	3.7 tons
Rated cap. R407C, Range N [kW]	16.5 kW
Rated cap. R407C, Range N [TR]	4.7 tons
Rated cap. R507, Range B [kW]	5.9 kW
Rated cap. R507, Range B [TR]	1.7 tons
Rated cap. R507, Range N [kW]	13 kW

5702422020400

EAN

Product family name	T2		
	P. Darie and R. Barrier	Rated cap. R507, Range N [TR]	3.7 tons
Product group	Expansion valves	Rated cap. R513A, Range N [kW]	6.9 kW
Product name	Orifice for expansion valve	Rated cap. R513A, Range N [TR]	2 tons
Quantity per packing format	25 pc	nated cap. no 13A, natige N [1N]	Z tons
Rated cap. cond. Range N [IMP]	tcond=100 °F tevap=40 °F tliq=98 °F	Refrigerants	R22/R407C R23 R236fa R407C R134a/R513A
Rated cap. cond. Range N [SI]	tcond=38 °C tevap=4.4 °C tliq=37 °C		R407A R448A R449A R452A
Rated cap. R134a, Range N [kW]	8.4 kW		R404A/R507A
Rated cap. R134a, Range N [TR]	2.4 tons	Serviceable	No
Rated cap. R22, Range B [kW]	7.3 kW	Temperature range [°C] [Max]	10 °C
Rated cap. R22, Range B [TR]	2.1 tons	Temperature range [°C] [Min]	-40 °C

Rated cap. R22, Range N [kW]	16.7 kW	Temperature range [°F] [Max]	50 °F
Rated cap. R22, Range N [TR] 4.8 tons	Temperature range [°F] [Min]	-40 °F	
	Туре	Orifice	
	Used for product	T 2 TE 2	