

RISCALDATORI E RIDUZIONI PER BOMBOLE



HOT-BLOWER

Soffiatore riscaldante

- Utilizzabile per asciugare le batterie alettate (condensatori- evaporatori).
- Ideale per riscaldare il refrigerante durante le fasi di trasferimento (da bombola a bombola e durante il recupero).

| Codice | Modello | Dimensioni | Peso |
|----------|------------|--------------------|--------|
| 14019019 | HOT-BLOWER | 195 x 170 x 190 mm | 1,6 kg |



Caratteristiche tecniche

| | |
|---------------------------------|-----------------------------------|
| Alimentazione | 230V-50/60Hz |
| Potenza | 550 W |
| Portata soffio | 2.7 m ³ /min |
| Temperatura max. | 45 °C |
| Protezione termica | Si |
| Interruttore di accensione | On/Off con pulsante di bloccaggio |
| Lunghezza cavo di alimentazione | 1.8 mt |



RSF400

Riscaldatore termostato per bombole

La resistenza viene fornita con due molle a corredo.

| Codice | Modello | Dimensioni | Peso |
|----------|----------------------|--------------------|---------|
| 14019007 | RSF 400/2T/CLASSE2 | 150 x 150 x 190 mm | 0,35 kg |
| 14023015 | Molla per resistenza | | |



Caratteristiche tecniche

| | |
|------------------------|-----------|
| Potenza | 400 W |
| Temperatura | 60 °C max |
| Lunghezza riscaldatore | 700 mm |
| Lunghezza molla | 80 mm |



Riduzioni per bombole



| Rif | Codice | Modello | Descrizione | Attacchi | |
|-----|-------------|---------|--|-------------------------------|-----|
| A | 05055009 | 816/2 | Riduzione | 21.8W-1/14" DX F x 1/4 SAE M | |
| A | 05108020001 | 816/2K | Kit 2 riduzioni con guarnizioni | 21.8W-1/14" DX F x 1/4 SAE M | 2 |
| B | 05055011 | 816/6 | Riduzione | 21.8W-1/14" DX F x 3/8 SAE M | |
| B | 05108067001 | 816/6K | Kit 2 riduzioni con guarnizioni | 21.8W-1/14" DX F x 3/8 SAE M | 2 |
| C | 05055022 | 816/5 | Riduzione | 21.8W-1/14" DX F x 5/16 SAE M | |
| C | 05108068001 | 816/5K | Kit 2 riduzioni con guarnizioni | 21.8W-1/14" DX F x 5/16 SAE M | 2 |
| D | 05055100 | W404/6 | Riduzione con guarnizione | 1/4 SAE F x 3/8 SAE M | 100 |
| D | 05108069001 | 404/6K | Kit 2 riduzioni con guarnizioni | 1/4 SAE F x 3/8 SAE M | 2 |
| E | 05055090 | W404/5 | Riduzione con guarnizione | 1/4 SAE F x 5/16 SAE M | 100 |
| E | 05108022001 | 404/5K | Kit 2 riduzioni con guarnizioni | 1/4 SAE F x 5/16 SAE M | 2 |
| F | 05055088 | 821/5 | Riduzione | 21.8W-1/14" SX F x 5/16 SAE M | |
| | 14020124001 | G/W404 | Kit 10 guarnizioni per W404/6 e W404/5 | - | 10 |

HEATERS AND ADAPTERS FOR BOTTLES



HOT-BLOWER

Hot blower

- Suitable to dry finned batteries (condensers-evaporators).
- Ideal to warm up the refrigerant during the transfer operations (from bottle to bottle and during recovery).

| Code | Model | Dimensions | Weight |
|----------|------------|--------------------|--------|
| 14019019 | HOT-BLOWER | 195 x 170 x 190 mm | 1,6 kg |



Technical features

| | |
|--------------------|-------------------------|
| Power supply | 230V-50/60Hz |
| Power | 550 W |
| Wind rate | 2.7 m³/min |
| Max. temperature | 45 °C |
| Thermal cut-out | Yes |
| Power switch | On/Off with lock button |
| Power cable length | 1.8 mt |

RSF400

Heater with thermostat

The heater is supplied with two springs.



| Code | Model | Dimensions | Weight |
|----------|--------------------|--------------------|---------|
| 14019007 | RSF 400/2T/CLASSE2 | 150 x 150 x 190 mm | 0,35 kg |
| 14023015 | Spring for heater | - | - |



Technical features

| | |
|---------------|-----------|
| Power | 400 W |
| Temperature | 60 °C max |
| Heater length | 700 mm |
| Spring length | 80 mm |



Adapters for bottles



| Ref | Code | Model | Description | Connections | |
|-----|-------------|--------|------------------------------------|-------------------------------|-----|
| A | 05055009 | 816/2 | Adapter | 21.8W-1/14" DX F x 1/4 SAE M | |
| A | 05108020001 | 816/2K | kit 2 adapters with gasket | 21.8W-1/14" DX F x 1/4 SAE M | 2 |
| B | 05055011 | 816/6 | Adapter | 21.8W-1/14" DX F x 3/8 SAE M | |
| B | 05108067001 | 816/6K | kit 2 adapters with gasket | 21.8W-1/14" DX F x 3/8 SAE M | 2 |
| C | 05055022 | 816/5 | Adapter | 21.8W-1/14" DX F x 5/16 SAE M | |
| C | 05108068001 | 816/5K | kit 2 adapters with gasket | 21.8W-1/14" DX F x 5/16 SAE M | 2 |
| D | 05055100 | W404/6 | Adapter with gasket | 1/4 SAE F x 3/8 SAE M | 100 |
| D | 05108069001 | 404/6K | kit 2 adapters with gasket | 1/4 SAE F x 3/8 SAE M | 2 |
| E | 05055099 | W404/5 | Adapter with gasket | 1/4 SAE F x 5/16 SAE M | 100 |
| E | 05108022001 | 404/5K | kit 2 adapters with gasket | 1/4 SAE F x 5/16 SAE M | 2 |
| F | 05055088 | 821/5 | Adapter | 21.8W-1/14" SX F x 5/16 SAE M | |
| | 14020124001 | G/W404 | Kit 10 gaskets for W404/6 e W404/5 | - | 10 |