

RAV-HM_1BTP

UNITA' INTERNA	RAV-HM561BTP-E	RAV-HM801BTP-E	RAV-HM1101BTP-E	RAV-HM1101BTP-E	RAV-HM1401BTP-E	RAV-HM1401BTP-E	RAV-HM1601BTP-E	
UNITA' ESTERNA	RAV-GP561ATW-E	RAV-GP801ATW-E	RAV-GP1101AT-E	RAV-GP1101AT8-E	RAV-GP1401AT-E1	RAV-GP1401AT8-E	RAV-GP1601AT8-E	
	Monofase	Monofase	Monofase	Trifase	Monofase	Trifase	Trifase	
RAFFRESCAMENTO								
Capacità nominale	kW	5.00	7.10	10.00	10.00	12.50	12.50	14.00
Capacità min. - max.	kW	1,20 - 5,60	1,90 - 8,00	3,10 - 12,00	2,60 - 12,00	3,10 - 14,00	2,60 - 14,00	2,60 - 16,00
Potenza assorbita (min - nom - max)	kW	0,19 - 1,52 - 1,99	0,26 - 1,63 - 3,20	0,65 - 2,40 - 3,63	0,66 - 2,58 - 4,01	0,65 - 3,57 - 3,97	0,66 - 3,81 - 4,89	0,66 - 4,49 - 6,50
Pdesignc	kW	5.00	7.10	10.00	10.00	12.50	12.50	n.d.
SEER	W/W	5.81	7.86	7.19	6.10	6.77	6.02	5.81
Classe di efficienza energetica		A+	A++	A++	A+	-	-	-
Consumo energetico stagionale	kWh	301.00	316.00	486.00	574.00	1107.00	1245.00	1444.00
RISCALDAMENTO								
Capacità nominale	kW	5.60	8.00	11.20	11.20	14.00	14.00	16.00
Capacità min. - max.	kW	0,90 - 7,40	1,30 - 11,30	2,60 - 13,00	2,40 - 15,60	2,60 - 16,50	2,40 - 18,00	2,40 - 19,00
Potenza assorbita (min - nom - max)	kW	0,16 - 1,61 - 2,76	0,20 - 1,85 - 3,55	0,47 - 2,73 - 3,38	0,53 - 2,76 - 4,42	0,47 - 3,63 - 4,43	0,53 - 3,66 - 5,71	0,53 - 4,57 - 6,50
Pdesignh	kW	3.80	5.10	9.20	n.d.	9.60	n.d.	n.d.
SCOP	W/W	4.27	4.85	4.30	4.19	4.29	3.99	3.96
Classe di efficienza energetica	H	A+	A++	A+	A+	-	-	-
Consumo energetico stagionale	kWh	1245.00	1472.00	2997.00	3606.00	3133.00	4143.00	4238.00
UNITA' INTERNA	RAV-HM561BTP-E	RAV-HM801BTP-E	RAV-HM1101BTP-E	RAV-HM1101BTP-E	RAV-HM1401BTP-E	RAV-HM1401BTP-E	RAV-HM1601BTP-E	
Portata Aria (b - m - a)	m ³ /h	480 - 630 - 800	720 - 930 - 1200	1260 - 1650 - 2100	1260 - 1650 - 2100	1260 - 1650 - 2100	1260 - 1650 - 2100	
Prevalenza statica utile (min - nom - max)	Pa	30 - 30 - 120	30 - 30 - 120	30 - 40 - 150	30 - 40 - 150	30 - 50 - 150	30 - 50 - 150	
Livello di pressione sonora (b - m - a)	dB(A)	25 - 29 - 33	26 - 30 - 34	33 - 36 - 40	33 - 36 - 40	33 - 36 - 40	33 - 36 - 40	
Livello di potenza sonora (b - m - a)	dB(A)	40 - 44 - 48	41 - 45 - 49	48 - 51 - 55	48 - 51 - 55	48 - 51 - 55	48 - 51 - 55	
Pompa scarico condensa		inclusa	inclusa	inclusa	inclusa	inclusa	inclusa	

Prevalenza pompa	mm	850.00	850.00	850.00	850.00	850.00	850.00	850.00
Dimensioni (A × L × P)	mm	275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750
Peso	kg	23.00	30.00	40.00	40.00	40.00	40.00	40.00
Flangia di mandata aria	Codice	TCB-SF56C6BPE	TCB-SF80C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE	TCB-SF160C6BPE
Numero Bocchette		2.00	3.00	4.00	4.00	4.00	4.00	4.00
UNITA' ESTERNA		RAV-GP561ATW-E	RAV-GP801ATW-E	RAV-GP1101AT-E	RAV-GP1101AT8-E	RAV-GP1404AT-E	RAV-GP1401AT8-E	RAV-GP1601AT8-E
Portata Aria (a) (C - H)	m³/h	2250.00	3180.00	6960.00	6060.00	6960.00	6180.00	6180.00
Livello di pressione sonora (C - H)	dB(A)	46 - 48	46 - 48	49 - 50	49 - 50	50 - 51	51 - 52	51 - 53
Livello di potenza sonora (C - H)	dB(A)	63 - 65	63 - 65	66 - 67	66 - 67	67 - 68	68 - 69	68 - 70
Intervallo di funzionamento (C)	°C	-15 ÷ 52	-15 ÷ 52	-15 ÷ 52	-15 ÷ 46	-15 ÷ 52	-15 ÷ 46	-15 ÷ 46
Intervallo di funzionamento (H)	°C	-27 ÷ 15	-27 ÷ 15	-27 ÷ 15	-20 ÷ 15	-27 ÷ 15	-20 ÷ 15	-20 ÷ 15
Dimensioni (A × L × P)	mm	630 x 799 x 299	1050 x 1010 x 370	1550 x 1010 x 370	1340 x 900 x 320	1550 x 1010 x 370	1340 x 900 x 320	1340 x 900 x 320
Peso	kg	45.00	74.00	104.00	95.00	104.00	95.00	95.00
Compressore		DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary
Refrigerante-Precarica Kg-TCO2Eq-GWP		R32 - 1,35 - 0,91 - 675	R32 - 1,9 - 1,28 - 675	R32 - 3,1 - 2,09 - 675	R32 - 2,6 - 1,76 - 675	R32 - 3,1 - 2,09 - 675	R32 - 2,6 - 1,76 - 675	R32 - 2,6 - 1,76 - 675
Accoppiamento a cartella Gas		1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
Accoppiamento a cartella Liquido		1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Lunghezza delle tubazioni (min - max)	m	3 - 50	3 - 50	3 - 75	3 - 75	3 - 75	3 - 75	3 - 75
Dislivello massimo	m	30.00	30.00	30.00	30.00	30.00	30.00	30.00
Lunghezza delle tubazioni senza carica aggiuntiva	m	20.00	30.00	30.00	30.00	30.00	30.00	30.00
Alimentazione	V-ph-Hz	220/240 - 1 - 50	220/240 - 1 - 50	220/240 - 1 - 50	380/415 - 3 - 50	220/240 - 1 - 50	380/415 - 3 - 50	380/415 - 3 - 50
Corrente massima	A	13.10	20.70	22.80	16.20	22.80	16.50	16.90
Detraibilità fiscale		-	0.65	0.65	0.65	0.65	0.65	-
Conto Termico		-	CT	CT	CT	CT	CT	-

The specification may be subject to change without notice for purpose of improvement.