

BARRIERE D'ARIA

SERIE ECOLINE



Con telecomando



- Dispositivo apertura/chiusura porte
- Installazione 2,5 ÷ 3,5 m
- Multispeed • Alimentazione 220V/1/50Hz

Cod.	Lunghezza [mm]	Input power [W]	Veloc. aria [m/s]	Portata d'aria [m ³ /h]	Rumorosità [db]	Peso netto [kg]	Dimensioni [mm]
1S.791A	900	90 ÷ 110	9 ÷ 10,5	1000 ÷ 1250	51 ÷ 53	6,50	910x176x175
1S.792A	1200	130 ÷ 155	9 ÷ 10,5	1450 ÷ 1800	53 ÷ 55	8	812x12x176x175
1S.793A	1500	170 ÷ 200	9 ÷ 10,5	1850 ÷ 2350	54 ÷ 56	9,50	1515x176x175
1S.794A	1800	205 ÷ 245	9 ÷ 10,5	2300 ÷ 2900	55 ÷ 57	11,50	1817x176x175
1S.795A	2000	235 ÷ 275	9 ÷ 10,5	2500 ÷ 3150	56 ÷ 58	13,00	2000x176x175

Con resistenza - Alimentazione 220-380/3/50

Cod.	Lunghezza [mm]	Input power [W]	Potenza assorbita [kW]	Veloc. aria [m/s]	Portata d'aria [m ³ /h]	Peso netto [kg]	Dimensioni [mm]
1S.708A	900	90	6	6	1000	11,00	910x176x175
1S.709A	1200	120	8	6	1350	13,50	1212x176x175
1S.710A	1500	150	10	6	1700	16,00	1515x176x175
1S.735A	1800	180	12	6	2050	19,00	1817x176x175
1S.736A	2000	240	14	6	2050	25,00	2026x176x175