

Model	Indoor Unit		MFA2U-17HRFNX(GA)
	Outdoor Unit		MOX330U-18HFNB-Q(GA)
Power Supply		V/O/Hz	220-240 / 1 / 50
Capacity	Cooling	kW	4.98 (2.64 ~ 5.57)
	Heating		5.28 (2.20 ~ 6.30)
Power Input	Cooling / Heating	kW	1.50 (0.65 ~ 1.95) / 1.42 (0.60 ~ 1.90)
SEER	Cooling	W/W	6.7
SCOP	Heating		4.0
Energy Efficiency Class	Cooling		A++
	Heating		A+
Running Current	Cooling/ Heating	A	6.70 (2.95 ~ 8.70) / 6.40 (2.75 ~ 8.50)
Air Flow (indoor unit)		m ³ /h	780 / 690 / 600
Sound Pressure (indoor unit)		dB(A)	41 / 38 / 32
Sound Power (indoor unit)		dB(A)	55
Air Flow (outdoor unit)		m ³ /h	2100
Sound Pressure (outdoor unit)		dB(A)	55
Sound Power (outdoor unit)		dB(A)	63
Dimensions W x D x H Weight	Indoor Unit	mm	794 x 206 x 621
		kg	14.9
	Outdoor Unit	mm	805 x 330 x 554
		kg	32.5
Refrigerant piping (liquid/gas)		mm	6.35 / 12.7
Max. refrigerant pipe length		m	30
Max. difference in level			20
Operation Temperature	Cooling	°C	-15 ~ 50
	Heating		-15 ~ 24
Refrigerant / Charged (kg)			R32 / 1.15